



MANUFACTURED IN CANADA

ABOUT THE BRUSH MULCHER

- Designed to mulch branches, light timber, saplings, brush, and other tough vegetation
- Hinged rubber containment guard
- 2 position hitch, center or 14" offset to right
- Indexable teeth that can easily be replaced
- · Single carbon fiber timing belt
- Adjustable ledger bar

- High strength steel housing
- Adjustable skid shoes
- · Engineered for quick, hassle-free maintenance
- 540 rpm PTO
- Machined anti-wrap protection
- Remote grease fittings to easily grease bearings



WEARSHARP© TOOTH	- 1
Carbidatin	

- V Carbide tip • Indexable 3 times for extended use

	_
Brush Mulcher	BRM60
Overall Width	72"
Rotor Width	60"
Tractor Recommended HP	30 TO 50
Maximum HP	50
Three Position Cutting depth	1" BELOW, LEVEL, 1" ABOVE
Cutters	INDEXABLE CARBIDE
Number of Cutters	72
Rotor Diameter (tooth tips)	16-1/2"
Hitch Size	CAT 1
Quick Hitch Compatible	YES
Unit Weight (lbs)	1,100
Hydraulic Requirement	NO

Universal Options	Part Number
Push Bar (3 Position Manual)	BRM60PB
Push Bar (Hydraulic)	BRM60PBHYD
Hydraulic Deflector	BRM60DF

OPTIONS



PUSH BAR

- Optional push bar guides trees and saplings to fall safely away from the tractor, ensuring controlled, safer mulching
- 3 position manual adjustment as standard
- A hydraulic cylinder is available as an upgrade for an additional cost



HYDRAULIC DEFLECTOR

- Deflector controls flying debris
- Hydraulic Deflector option requires hydraulic remotes for operation
- Increases mulching, decreases debris size

Reist Industries

100 Union Street Elmira, Ontario, Canada N3B 3L7

Phone: 519-669-1501 Toll Free: 1-877-467-3478 www.reistindustries.com