

ROTORAKE
Power Rake

ROTORAKE



*Shown with optional
Remote Controlled Hydraulic Kit*

REIST
INDUSTRIES

MANUFACTURED IN CANADA



THE DIFFERENCE IS QUALITY

The RotoRake from Reist Industries is a hydraulically driven power rake with features such as the dual motor design, 25° angle and 28° tilt, and bi-directional motor. With features like that, you can rest assured that the RotoRake will give you a quality result.

Pulverizing soil, leveling and finish grading top soil and gravel, removing debris, creating ditches and swales, and even scarifying ice in the winter has never been easier with the RotoRake from Reist Industries.

STANDARD FEATURES

- Jack Stand
- Lifting Lug for Easy Loading
- Side Shields
- Oscillating and Locking Wheels

OPTIONS

- CAT 1 & 2 3PH Plate
- Side Cutters
- 12V Electric Valve & Hydraulic Cylinder Kit (Angle)
- 12V Electric Valve & Hydraulic Cylinder Kit (Tilt & Angle)
- Angle Cylinder & Hose Kit (3PH)
- Tilt Cylinder & Hose Kit (3PH & PTO)

RotoRake	RR48	RR48-R	RR60	RR72	RR84
Dimensions (WLH)	57 X 55 X 28"	57 X 55 X 28"	69 X 63 X 34"	81 X 63 X 34"	93 X 63 X 34"
Working Width	48"	48"	60"	72"	84"
Working Width (Angled 25°)	44"	44"	55"	65"	76"
Weight (lbs)	725	725	1,150	1,220	1,280
Cont. PSI	3,000 MAX	3,000 MAX	3,000 MAX	3,000 MAX	3,000 MAX
PTO Required	N/A	N/A	N/A	N/A	N/A
Roto Speed	230-450 RPM	230-450 RPM	230-450 RPM	230-450 RPM	230-450 RPM
Hyd. GPM Range	12-20	12-20	18-30	18-30	18-30
Rotor Torque @ 2500 PSI	550 FT-LBS	550 FT-LBS	550 FT-LBS	550 FT-LBS	550 FT-LBS
Mount Type	MINI SKIDSTEER (BOBCAT)	MINI SKIDSTEER	STD. SKIDSTEER	STD. SKIDSTEER	STD. SKIDSTEER
Gauge Wheels Included	1	1	2	2	2
Tilt	N/A	N/A	MANUAL	MANUAL	MANUAL
Angle	MANUAL	MANUAL	MANUAL	MANUAL	MANUAL



RR48 Model Shown

RR84 Model Shown with optional Remote Controlled Hydraulic Kit



BI-DIRECTIONAL ROTOR

The RotoRake's 10" diameter hydraulic bi-directional rotor allows for operation in both directions, making it easier to clear your land reducing the time needed to start your next pass.



RR84 Model Shown with optional Remote Controlled Hydraulic Kit

FLOATING ROTOR DESIGN

The RotoRake is equipped with dual motors providing up to 40% more torque. The motors connect to the rotor in a unique floating drive design, protecting the motor bearings.



25° ANGLE

The RotoRake features a manual 25° angle each direction. This makes the RotoRake ideal for both swaling and ditching.



SIDE CUTTERS *(Optional)*

The side cutters provide extra reach beyond the rotor to widen your clearing path, and to start the ditch when ditching. They pin on either the front or back of the RotoRake to face the direction you're traveling.



TUNGSTEN CARBIDE TEETH

The teeth are made from tough tungsten carbide and are welded to the rotor. To improve their pulverizing ability, the teeth are pointed and hold their edge for years.



ADJUSTABLE SIDE SHIELDS

The 2-position adjustable side shields direct material into the rotor and keep material from spilling out over the ends of the rotor leaving you a nice clean swath. When grading, these side shields turn the RotoRake into a box grader.



28° TILT

The RotoRake features a manual 28° tilt. This makes the RotoRake ideal for both swaling and ditching.



REMOTE-CONTROLLED HYDRAULIC KIT *(Optional)*

This hydraulic option for the RotoRake allows you to control the tilt and angle of the RotoRake from within the cab. You can choose either one or both of these options.

ROTORAKE

PTO Model



RR84PTO18G Model Shown

The PTO RotoRake from Reist Industries allows you to connect our reliable power rake to your tractor's PTO system. Utilizing the same features and options as the skidsteer model, the PTO model also features oscillating gauge wheels which lock in the level position for PTO use.

RotoRake P.T.O	RR60PTO18G	RR72PTO18G	RR84PTO18G
Dimensions (WLH)	69 X 63 X 34"	81 X 63 X 34"	93 X 63 X 34"
Working Width	60"	72"	84"
Working Width (Angled 25°)	55"	65"	76"
Weight (lbs)	1,350	1,420	1,500
Cont. PSI	3,000 MAX	3,000 MAX	3,000 MAX
PTO Required	540RPM	540RPM	540RPM
Roto Speed	230-450 RPM	230-450 RPM	230-450 RPM
Hyd. GPM Range	18-30	18-30	18-30
Rotor Torque @ 2500 PSI	550 FT-LBS	550 FT-LBS	550 FT-LBS
Mount Type	3PH CAT 1 & 2	3PH CAT 1 & 2	3PH CAT 1 & 2
Gauge Wheels Included	2	2	2
Tilt	MANUAL	MANUAL	MANUAL



OSCILLATING GAUGE WHEELS

Oscillating gauge wheels lock in level position for the (PTO) three point hitch use.



PTO DRIVEN ROTOR

Power take-off for your RotoRake unit drives a pump which drives the rotor motors.

Reist Industries

100 Union Street
Elmira, Ontario, Canada
N3B 3L7

Phone: 519-669-1501
Fax: 519-669-3021
Toll Free: 1-877-467-3478
www.reistindustries.com